

## PA960-2170 20 Watt Power Amplifiers



## **Key Features**

- Power Amplifiers designed for GSM Testing
- Two models PA960 and PA2170
- PA960 covers 890 960 MHz
- PA2170 covers 1710 2170 MHz
- 20 Watts Output
- 23 dB Gain
- AGC gives stable gain to  $\pm 0.5 \text{ dB}$
- Short and Open Circuit Protection
- Matching Signal Generators Available

## **General Description**

EST SYSTEMS

The PA960 and PA2170 power amplifiers are designed for UMTS and GSM testing. They produce up to 20 Watts output from a +20 dBm input, thus they have a gain of 23 dB. Two models cover 890 - 960 MHz and 1710 - 2170 MHz.

They can either be used with any standard signal generator, or matching signal generators from Precision Test Systems are available. The FSG960B covers 890 - 960 MHz and the FSG2170 covers1710 - 2170 MHz. Bothe FSG models can generate an output level from -20 dBm to +20 dBm in 20 dB steps.

An automatic gain control (AGC) circuit inside the power amplifiers ensures flatness is typically better than  $\pm$  0.5 dB.

The power amplifiers are protected against open circuits, short circuits or poor VSWR's.

The amplifiers are housed in an aluminum case and are powered from a 100 - 240 VAC power source.

Description	Specification	Remarks
	Amplifier	
Frequency Range (PA960)	890 - 960 MHz	Usable 800 - 1000 MHz
Frequency Range (PA2170)	1710 - 2170 MHz	
Input Impedance	50 Ω	PA960 typically < 0.5 dB
Input Return Loss	> 15 dB typical	
Output Impedance	50 Ω	
Output Return Loss	> 12 dB typical	
Gain	23 dB nominal	
Gain Flatness (AGC Enabled)	$\pm 1 \text{ dB}, \pm 0.5 \text{ dB}$ typical	
Maximum Input	+23 dBm	
Output Power with +20 dBm input	+43 dBm (20 Watts)	
	Miscellaneous	
Operating Temperature	0 °C to +40 °C	
Storage Temperature	-20 °C to $+60$ °C	
Power Inlet with switch	IEC320 power cord	Rear Panel
AC Voltage Range	100 - 240 VAC (usable 90-260 VAC)	
Power consumption	100 watts max	
Fuse rating	3.15A, 250 VAC slow blow type	
Dimensions		
Width	275 mm	
Depth	330 mm	
Height	88 mm	
Weight	4 kg	
0	Consult Precision Test Systems for further de	etails

Head Office - UK	South Africa	USA
Precision Test Systems LTD	Precision Test Systems cc	Precision Test Systems L.L.C
The Studio, Whitehouse Farm	Gauteng	304 S. Jones Blvd
New Hall Lane, Mundon	South Africa	Suite #807
Maldon, Essex, CM9 6PJ, UK.	Fax: 08651 58198	Las Vegas, NV, 89107
Tel: +44 (0) 870 368 9608	Email: sasales@ptsyst.com	Tel: 1 888 876 4804
Fax: +44 (0) 1245 330030	Web: www.ptsyst.com	Fax: 1 832 201 6564
Email: uksales@ptsyst.com		Email: usasales@ptsyst.com
Web: www.ptsyst.com		Web: www.ptsyst.com

Specifications and features subject to change without notice (150816)